

A multiple drum puller, the Wagner-Smith Equipment Co. **Model T-4DP-115** can be used in a wide range of Transmission stringing applications.

## OPERATING FEATURES

- Internally pressure compensated closed-loop hydraulic system, minimizes heat build up of hydraulic fluid while in the tensioning mode.
- The preset desired pulling or tensioning pressure can be easily set.
- Spring applied, hydraulic pressure released safety brake is standard in the main drive line for operator safety.
- All unit operating controls are located at the operator's station, off the ground, for operator safety.



## MODEL T-4DP-115 SPECIFICATIONS

### STANDARD FEATURES

- Engine 115 hp class tier III, water cooled Diesel.
- Front Hitch Adjustable 3" lunette Eye
- Lighting D.O.T. Regulation (LED)
- Electrical Plug 7-way pin
- Towing Standard ½" high test chain
- Front Jack Manual 2-Speed crank type
- Rear Jacks Manual drop pin type
- Tires/Wheels(8) 255/70R 22.5 Load Range "H" 22.5 X 8.25
- Axles (2) 22,500 lbs. each
- Suspension Slipper leaf spring
- Brakes Air brakes with ABS front axle.
- Drive Clutches (4) independent—manual
- Wheel Chocks 2 each with storage brackets.
- Tie Downs Front & rear frame mounted.
- Grounding Lugs Mounted front & rear or unit.
- Hydraulic Tank 40 gallons
- Fuel Tank 19 gallons

### OPTIONS AVAILABLE

- Hydraulic Operated Front and Rear Jacks
- Vandalism Package
- Skid: Estimated Weight w/o Rope: 20,140 lbs.
- Extra 1,500' of 5/8" synthetic rope may be added to each reel

### UNIT PERFORMANCE (standard pulling reel)

- Continuous Torque Rating 115,000 in. lbs
- Line Speed (Average) 5 mph
- Full Drum Line Rating 3,600 lbs. (w / 5/8" synthetic rope)  
4,100 lbs. (w / 3/8" Amsteel® Blue)

### STANDARD PULLING REEL

- Quantity Four (4)
- Diameter (OD) 64"
- Inside Width 22"
- Core Diameter 20"
- Approx. Line Capacity 15,000' of 5/8" synthetic rope  
22,000 ft. of 3/8" Amsteel® Blue

### DIMENSIONS & WEIGHT

- Unit Length 23'6"
- Unit Width 8'
- Unit Height 11'3"
- Shipping Height 10'
- Net Weight w/o Rope 24,450 lbs.
- GVWR 34,460 lbs.
- GAWR 32,000 lbs.
- Tongue Weight 2,520 lbs.