

The Wagner-Smith Equipment Co. **Model CRR-35** is an electric powered reel roller for take-up or payout of conductor or rope on or from a reel. It can be mounted to a flat bed truck or trailer as well as placed on the ground for its purpose.



OPERATING FEATURES

- Truck, trailer or free standing mounting
- Cable reel roller has integral tie-downs and reel anchor points
- The adjustable roller permits the unit to accommodate reel diameters from 30" to 156" (13ft) by 100" wide.
- The reel roller frame is equipped with integral forklift lifting points for safety.
- The reel roller is equipped with a stowage compartment for the control console.
- On/off foot actuated control switch
- Panel mounted speed control and reversing switch

STANDARD FEATURES

- Adjustable Roller (Bolt-On) 30" to 156" diameter X 100"
- Electrical Power Required 110-120 VAC 60Hz. 15 amps
- Speed Control Panel mounted from 0 — 70 rpm
- Reverse Switch Panel mounted
- Control Switch Foot actuated on/off
- Fused Circuit 15A Slo-Blow fuse (Bussmann® MDA-15A)
- Power Cord HD neoprene covered X 66 in.
- Console Remote Cord HD neoprene covered X 120 in.
- Reel Tie Downs (4) 3" diameter
- Unit Tie Downs (4) 3¾" diameter

MODEL CRR-35 SPECIFICATIONS

UNIT PERFORMANCE

- Max. Reel Diameter 156"
- Max. Reel Width 100"
- Max. Reel Weight 35,000 lbs.
- Roller Diameter (s) 6"
- Roller Flange Diameter (s) 15" Drive Roller, 11½" Idler Roller

DIMENSIONS & WEIGHT

- Unit Length 69"
- Unit Width 116"
- Unit Height 22"
- Net Weight 2,465 lbs.

