

The Wagner-Smith Equipment Co. **Model T-BWT-10-60** is a trailer mounted 60 in. diameter single conductor bullwheel tensioner. The bullwheels are canted to minimize line twisting. Maximum line tension rating is 10,000 lbs. and an average 4 mph line speed. This is a great unit for Transmission jobs.

OPERATING FEATURES

- Bullwheel brakes are smooth running hydraulic calipers.
- All unit operating controls are located at the operator's station, off the ground, for operator safety.
- Large diameter fairlead roller assembly is provided to reduce bending radius on input side.



MODEL T-BWT-10-60 SPECIFICATIONS

STANDARD FEATURES

- Tension Brakes Hydraulic actuated caliper/48 in.
- Dia. Front Hitch Adjustable 3" lunette eye
- Lighting DOT regulation (LED)
- Electrical Plug 6-way pin
- Front Jack Manual crank type
- Rear Jacks Manual pin type
- Tires 215/75R17.5 Load Range "H"
- Axle(s) Tandem 8,000 lb. each
- Suspension Leaf spring
- Brakes Electric with breakaway switch
- Wheel Chocks 2 each with support brackets
- Tie Downs Front and rear on frame support

OPTIONS AVAILABLE

- 3 Groove elastomeric pads available

UNIT PERFORMANCE

- Maximum Tension Rating 10,000 lbs.
- Line Speed (Average) 4 mph

BULLWHEEL TENSIONER

- Diameter 60" (bottom of groove)
- Groove Diameter 2½ in.
- Number of Grooves 5
- Replaceable Segments Yes
- Bullwheel Lining Elastomer (bolt-on)
- Tensioning Brakes Hydraulic actuated caliper/ disc
- Brake discs 48" diameter

DIMENSIONS & WEIGHT

- Unit Length 20'
- Unit Width 8'
- Unit Height 9'11"
- Net weight 9,280 lbs.
- GVWR 18,800 lbs.
- GAWR 16,000 lbs.
- Tongue Load 2,700 lbs.