

OPERATING FEATURES

- Quick change type reel and spindle assemblies lift straight out of the unit without having to shift to the side. No tools are required for reel removal.
- Manual hydraulics
- Easy, one person operation
- Very simple maintenance
- Versatility in size of spool
- Designed with a low center of gravity
- Telescoping loading mechanism
- Hoses & wiring protected within frame
- Safety engineered



STANDARD FEATURES

- | | |
|-------------------|---|
| • Front Hitch | Adjustable 3" lunette eye |
| • Lighting | DOT regulation |
| • Electrical Plug | 6-way pin |
| • Front Jack | Manual crank type |
| • Tires | 235/75R17.5 |
| • Axle (s) | Stub axles |
| • Brakes | Electric with wet cell battery and breakaway switch |
| • Wheel Chocks | Wheel chocks with holders |
| • Reel Lift | Manual Hydraulics |

MODEL I-85 SPECIFICATIONS

UNIT PERFORMANCE - REEL CARRIER

- | | |
|--------------------------|-------------------|
| • Quantity | One (1) |
| • Max. Reel Diameter | 120" |
| • Max. Reel Width | 60" |
| • Trailer Payload Rating | 8,500 lbs. |
| • Spindle Diameter | 2-1/2" |
| • Reel Loading | Quick change type |

DIMENSIONS & WEIGHT

- | | |
|---------------|------------|
| • Unit Length | 11' |
| • Unit Width | 8' |
| • Net Weight | 1,600 lbs. |
| • GVWR | 8,500 lbs. |