

Tenex is a 12-strand single braid that offers high strength with low stretch and outstanding abrasion resistance. It is Samthane coated to provide enhanced wear life, snag resistance, and increased ease of splicing. It is a viable alternative to using double braids when easy field splicing and economy are major considerations.



FEATURES AND BENEFITS:

- > Available in long lengths
- > Easy to inspect
- > Easy to splice
- > Economical
- > Excellent abrasion resistance
- > Excellent snag resistance
- > Firm construction
- > High strength per diameter
- > High strength-to-weight ratio

APPLICATIONS INCLUDE:

- > Pulling / Stringing Line

PRODUCT CODE: 826

FIBER: Polyester

SPECIFIC GRAVITY: 1.38

SPLICE/CLASS: 12-Strand Class I

ELASTIC ELONGATION:

At percent of break strength

10%1.40%

20%2.30%

30%3.00%

COLOR OPTIONS:

Coated black, blue, clear, green, orange, red, or yellow



DIAM. (INCH)	CIRC. (INCH)	WEIGHT PER 100 FT. (LBS)	AVG. STRENGTH (LBS)	MIN. STRENGTH (LBS)
1/4	3/4	2.1	3,400	3,100
5/16	1	3.2	5,100	4,600
3/8	1 1/8	3.9	6,300	5,700
7/16	1 1/4	6.3	9,300	8,400
1/2	1 1/2	8	12,500	11,300
9/16	1 3/4	10	14,400	13,000
5/8	2	12	18,500	16,700
3/4	2 1/4	17.2	24,400	22,000
7/8	2 3/4	25.8	36,200	32,600
1	3	38.5	51,900	46,700
1 1/8	3 1/2	43	62,600	56,300
1 1/4	3 3/4	52.2	71,400	64,300
1 5/16	4	59.7	83,000	74,700
1 1/2	4 1/2	71.5	97,400	87,700

