



The Wagner-Smith Equipment Co. *Model MPT-*14 is an adjustable trailer designed to hold utility poles of various lengths or a 60" diameter reel.



### **OPERATING FEATURES**

- Telescoping frame designed to accommodate multiple pole lengths and maintain proper weight distribution.
- Movable rear and amidships bolsters adjust to keep load centered on trailer.
- Four (4) 5,400 cargo straps to secure poles during transport.
- Removable spindle with locking collars can accommodate a 60" diameter by 55" wide reel.

# **MODEL MPT-14 SPECIFICATIONS**

#### UNIT PERFORMANCE

•	Maximum	Reel	Diameter	e	50"
---	---------	------	----------	---	-----

• Maximum Reel Width 55"

### **DIMENSIONS & WEIGHTS**

• Unit length (retracted)	27'2"
• Unit length (extended)	37'2"
• Unit Width	7'8"
• Unit Height	5'10"
• Unit Height w/ 60" reel	7'8"
• Bolster Height	18 ¼"
• GAWR	12,780 lbs.
• GVWR	16,000 lbs.
• Empty Trailer Weight	4,360 lbs.
• Cargo Capacity - (Pole (s)	12,000 lbs.
• Cargo Capacity - (Reel )	10,000 lbs.

• Tongue Weight (empty):



620 lbs.

50014-12R

#### **REAR VIEW OF THE MPT-14**

## **STANDARD FEATURES**

- Front Hitch
- Electrical Connections
- Lighting
- Front Jack
- Tires (4)
- Rims (4)
- Axles
- Suspension
- Brakes
- Control Straps
- Towing
- Lines
- Wheel Chocks
- Tie Downs
- Grounding

16.5 X 6.75 HC (8 holes x 6.5") (2 ea.) 7,000 lb. Capacity

9.5 X 16.5 Load Range "E"

Adjustable 3" lunette eye

DOT Regulation (LED)

Manual crank type

6 pole plug with spring cable

Slipper Spring

protector.

- Electric Brakes
- Qty. (3 ea.) 4" Wide x 12K# Cargo Straps
  - Standard <sup>1</sup>/2" high test chain
  - Electric ran outside frame
- 2 each with storage brackets
- Front and rear frame mounted
  - Front and rear mounted

**1-800-666-6567**