



OPERATING FEATURES

This model is a must when installing innerduct for a cable network. Requested from our customers, this 10,000 lb. rated trailer is helping lay the infrastructure for tomorrow's information superhighway. Quick change type reel and spindle assemblies lift straight out of the unit without having to shift to the side. No tools are required for reel removal.



STANDARD FEATURES

- Front Hitch Adjustable 3" lunette eye
- Lighting DOT regulation
- Electrical Plug 6-way pin
- Front Jack Manual crank type
- Stabilizer Jacks Two crank type rear
- Tires 235/85R16E
- Axle (s) Tandem 6,000 lb. capacity each
- Suspension Slipper spring
- Brakes Electric with wet cell battery and breakaway switch
- Wheel Chocks Wheel chocks with holders



MODEL MR120X3 SPECIFICATIONS

UNIT PERFORMANCE - REEL CARRIER

- Quantity Three (3)
- Max. Reel Diameter 96"
- Max. Reel Width 60"
- Max. Reel Weight 5,000 lbs. (each)
- Trailer Payload Rating 12,000 lbs.
- Spindle Diameter 2½"
- Reel Loading Quick change type without tools

DIMENSIONS & WEIGHT

- Unit Length 26'5"
- Unit Width 8'
- Net Weight 2,850 lbs.
- GVWR 10,000 lbs.
- GAWR 12,000 lbs.