



Designed for demanding transmission work, the T-3DP-200-FT4 delivers high pulling power with steady, controlled tension over long runs. Its pressure-compensated hydraulic system maintains performance under load while integrated data logging captures critical pull information for job documentation. Built for crews who need power, precision, and proof.

Key Features

- Three independently clutched pulling drums
- Hydraulic overspin fly out brakes for controlled payout with or without engine running
- Hydrostatic drive with variable pressure control
- Electronic display showing line pull, line speed, and reel diameter

Unit Performance	
Line Speed	4 MPH
Steel Rope 3/8" X 25,000	Full Drum Pull Rating - 6,400 lbs.
Dyneema® 1/2" X 25,000*	Full Drum Pull Rating - 6,800 lbs.*
Standard Features	
Number of Reels	3
Drum Diameter	62"
Drum Inside Width	48"
Drum Core Diameter	32"
Engine	140 HP FT4
Freewheel - Braking	42" Disc - Hydraulic
Trailer Braking System	Air ABS brake system
Hydraulic Tank Capacity	100 gallon
Levelwind System	Hydraulically operated post type with swing out top roller
Drive Clutches	Jaws on drives
Fuel Capacity	35 gallon diesel

The Dyneema 1/2" x 25,000' line is not included with the rental unit; it is only available as a special-order item when purchasing the unit.

Towing	
Suspension	Heavy duty hutch/leaf spring
Configuration / Axle Rating	Tandem 22,500 lbs. each
Front Hitch	Fifth wheel
Jacks	Hydraulically operated
Trailer Electrical Connection	7 way socket
Grounding	Front/rear mounted lugs
Lighting	DOT regulation LED
Tie Downs	Qty (2) - 2 1/4" ID front
Dimensions & Weight	
Overall Dimensions (L x W x H)	33'10" x 8' x 13'6" (13' in transport mode)
Net Weight (empty)	35,320 lbs.
GAWR	34,000 lbs.
GVWR	59,200 lbs.
Tongue Weight	24,800 lbs. (Full drum with rope)

Rental Item #: **41200-15R**

For additional details on the T-3DP-200-FT4, view the operator's [manual](#).