



A heavy-duty three drum puller, the Wagner Smith Equipment Co. **Model T-3DP-300-FT4** can be used in a wide range of Transmission stringing applications.

The internal pressure compensated closed-loop hydraulic system minimizes heat build up of hydraulic fluid and can preset desired pulling pressure. A spring applied, hydraulic pressure released safety brake is standard in the main drive line for operator safety.

All unit operating controls are located at the operators station, off the ground, for operator safety. Touchscreen display/electronics package — Now logs pull data, limits customer from damaging equipment because of “over limit” function. User can now see engine alerts and more detailed system alerts. This is a custom program created exclusively for WSE to communicate with FT4 engines and provide a better operating experience for the user.

Fold down safety screen and seat are all included as standard features. Each drum can be disconnected for freewheeling with brake over spin control. Hydraulic pressure control, drum speed control and gauges are panel mounted.

### STANDARD FEATURES

- Levelwind Hydraulic post type with swing out top roller, hydraulically operated from control stand
- Engine 173 HP class Final Tier 4, water cooled diesel
- Front Hitch Fifth wheel hitch
- Lighting DOT regulation, LED lights
- Electrical Socket 7-way pin
- Front Jack Manual 2-speed landing gear
- Tires 455/55R22.5 load range “L”
- Axles (s) Tridem 20,000 lbs. each
- Suspension Heavy Duty Hutch / Leaf spring
- Brakes Full Air w/ABS Brake system
- Grounding Mounted front and rear lugs
- Fuel Tank 35 Gallon Diesel
- Hyd. Res. 100 Gallon Reservoir
- Freewheeling 42” diameter brake disc
- Tie Downs Front & rear frame mounted

### OPTIONS AVAILABLE

- Canvas Reel cover



### MODEL T-3DP-300-FT4 SPECIFICATIONS

#### UNIT PERFORMANCE (Standard Pulling Drum)

- Continuous Torque Rating 300,000 in. lbs.
- Line Speed (average) 4 mph
- Full Drum Line Pull Rating 10,000 lbs.

The above figures are for a single drum pulling. Levelwind provided is set up for pulling one drum at a time. Full drum pull rating only applies to ½” steel rope

#### STANDARD PULLING DRUM (QUANTITY 3)

- Diameter (OD) 58”
- Inside Width 48”
- Core Diameter 32”
- Maximum Line Capacity 25,000’ of ½” steel rope

#### DIMENSIONS & WEIGHT (Standard Pulling Reel)

- Unit Length 35’ 8”
- Unit Width 8’ 0”
- Unit Height 13’ 6” (towing)
- Unit Weight (Empty) 41,900 lbs.
- GAWR 60,000 lbs.
- GVWR 82,900 lbs.
- Tongue Weight 31,003 lbs. (full drum wire rope)



Integrated touch screen allows operator easy access to controls, system/usage data and equipment manuals.