



A multiple drum puller, the Wagner-Smith Equipment Co. *Model T-4DP-115* can be used in a wide range of Transmission stringing applications.

# **OPERATING FEATURES**

- Internally pressure compensated closed-loop hydraulic system, minimizes heat build up of hydraulic fluid while in the tensioning mode.
- The preset desired pulling or tensioning pressure can be easily set.
- Spring applied, hydraulic pressure released safety brake is standard in the main drive line for operator safety.
- All unit operating controls are located at the operator's station, off the ground, for operator safety.

### STANDARD FEATURES

• Engine 115 hp class tier III, water cooled Diesel.

Front Hitch Adjustable 3" lunette EyeLighting D.O.T. Regulation (LED)

• Electrical Plug 7-way pin

Towing Standard ½" high test chain
 Front Jack Manual 2-Speed crank type
 Rear Jacks Manual drop pin type

• Tires/Wheels(8) 255/70R 22.5 Load Range "H"

22.5 X 8.25

Axles (2)SuspensionSlipper leaf spring

• Brakes Air brakes with ABS front axle.

Drive Clutches
 Wheel Chocks
 Tie Downs
 Grounding Lugs
 (4) independent—manual
 2 each with storage brackets.
 Front & rear frame mounted.
 Mounted front & rear or unit.

Hydraulic TankFuel Tank40 gallons19 gallons

# **OPTIONS AVAILABLE**

• Hydraulic Operated Front and Rear Jacks

• Vandalism Package

• Skid: Estimated Weight w/o Rope: 20,140 lbs.

• Extra 1,500' of 5/8" synthetic rope may be added to each reel



## **MODEL T-4DP-115 SPECIFICATIONS**

### **UNIT PERFORMANCE (standard pulling reel)**

• Continuous Torque Rating 115,000 in. lbs

• Line Speed (Average) 5 mph

• Full Drum Line Rating 3,600 lbs. (w / 5%" synthetic rope)

4,100 lbs. (w / 3/8" Amsteel® Blue)

#### STANDARD PULLING REEL

Quantity Four (4)
Diameter (OD) 64"
Inside Width 22"
Core Diameter 20"

• Approx. Line Capacity 15,000' of 5%" synthetic rope

22,000 ft. of 3/8" Amsteel® Blue

#### **DIMENSIONS & WEIGHT**

Unit Length 23'6"
Unit Width 8'
Unit Height 11'3"
Shipping Height 10'

Net Weight w/o Rope
 GVWR
 GAWR
 Tongue Weight
 24,450 lbs.
 34,460 lbs.
 32,000 lbs.
 2,520 lbs.







