



The Wagner-Smith Equipment Co. **Model T-4DP-36-FT4** is a small, compact, high-performance puller that is both economical and very versatile in use.

## OPERATING FEATURES

- Internally pressure compensated closed-loop hydraulic system, minimizes heat build up of hydraulic fluid while in the tensioning mode
- The preset desired pulling pressure can be easily set
- Spring applied, hydraulic pressure released safety brake is standard in the main drive line for operator safety
- All unit operating controls are located at the operator's station, off the ground, for operator safety
- Steel pulling drums, automatic levelwind assembly, freewheeling 18 in. ASTM 588 steel disk brake, safety screen and adjustable seat are all included as standard features

## STANDARD FEATURES

- Engine 36 hp water cooled diesel
- Front Hitch Adjustable 3" lunette eye
- Levelwind Automatic diamond lead screw
- Lighting D.O.T. regulation (LED)
- Front Jack Manual 1-speed crank type
- Rear Jacks Manual drop pin type
- Tires 215/75R 17.5 load range H
- Drive Clutches 4 independent manual on reels
- Single Axle 10,000 lbs. capacity
- Suspension Leaf spring
- Brakes Electric w/ breakaway switch
- Grounding Lugs Mounted front and rear

## OPTIONS AVAILABLE

- Dual diamond lead screw & sheave levelwind
- Hydraulic operated front and rear jacks



## MODEL T-4DP-36-FT4 SPECIFICATIONS

### UNIT PERFORMANCE (STD PULLING REEL)

- Continuous torque rating 36,000 in. lbs.
- Line speed (average) 4 mph
- Actual full drum pull rating 2,000 lbs.

### STANDARD PULLING REEL

- Quantity Four (4)
- Diameter (OD) 36"
- Inside width 23"
- Core diameter 10.75"
- Approx. line capacity 8,000 ft. of 1/2" synthetic rope

### DIMENSIONS & WEIGHT

- Unit length 15'8"
- Unit width 8' 1"
- Unit height 8'5"
- Net weight w/o rope 7,280 lbs.
- GVWR 10,800 lbs.
- GAWR 9,610 lbs.
- Tongue weight: 1,500 lbs.



Pulling End of the T-4DP-36-FT4

1-800-666-6567

wagnersmithequipment.com



41036-15R