

T-4RC-72X52-20

A trailer mounted, four place reel carrier used for Distribution, the Wagner-Smith Equipment Co. *Model T-4RC-*72x52-20 is designed to transport and tension cable or conductor reels up to 72" in diameter, 52" wide, and weighing up to 5,000 pounds per reel.

OPERATING FEATURES

- Quick change type reel and spindle assemblies lift straight out of the unit without having to shift to the side. No tools are required for reel removal.
- Reel spindles may incorporate an <u>optional</u> mechanical manual rewind to allow the operator to rewind conductor via a hand crank or external hydraulic supply when job is completed.

6-way pin

Manual crank type

Manual pin type

Slipper spring

ASTM 588 steel

Mounted front and rear

Front and rear frame mounted

Adjustable 3" lunette eye

235/75R17.5 Load Range "H"

Tandem 12,000 lb. Capacity each



STANDARD FEATURES:

- Front Hitch
- Lighting DOT Regulation (LED)
- Electrical Plug
- Front Jack
- Rear Jacks
- Tires
- Axle (s)
- Suspension
- Brakes Electric with breakaway switch
- Grounding Lugs
- Wheel Chocks Wheel chocks with holders
- Tie Downs
- Brake Discs

OPTIONS

- Mechanical manual rewind
- Hydraulic drive motor assembly



MODEL T-4RC-72X52-20 SPECIFICATIONS

Four (4)

UNIT PERFORMANCE - REEL CARRIER

- Quantity
- Max. Reel Diameter
- Max. Reel Width
- Max. Reel Weight
- Spindle Diameter
- Reel Brakes
- Reel Loading

72"
52"
5,000 lbs. (each)
2-3/4 in. w/ locking collars
Manually actuated caliper 16 in. dia. Disc
Quick change type without altering reel brake adjustment.

DIMENSIONS & WEIGHT:

Unit Length	31'7"
• Unit Width	8'
• Unit Height	7'7"
• Net Weight	7,480 lbs.
• GVWR	28,141 lbs.
GAWR	24,000 lbs.
Tongue Load	1,220 lbs.

1-800-666-6567 wagnersmithequipment.com



47072-17R