



A heavy-duty five drum puller, the Wagner Smith Equipment Co. **Model T-5DP-120** can be used in a wide range of Transmission stringing applications.

OPERATING FEATURES

- Internally pressure compensated closed-loop hydraulic system, minimizes heat build up of hydraulic fluid, can preset desired pulling pressure.
- Spring applied, hydraulic pressure released safety brake is standard in the main drive line for operator safety.
- All unit operating controls are located at the operator's station, off the ground, for operator safety.
- Each drum can be disconnected for freewheeling with brake over spin (manual) control. Drum brakes.

STANDARD FEATURES

- Levelwind Individual Hydraulic post type with swing-out top roller, hydraulically operated from control stand, each operates independently.
- Clutches Individual Hydraulic shifter for each reel
- Engine 115 HP class Tier 3, water cooled. Diesel
- Front Hitch Fifth wheel hitch
- Lighting DOT regulation, LED lights
- Elect. Socket 7-way pin
- Front Jack Manual 2-speed landing gear
- Tires 255/70R22.5 load range "G"
- Axles(s) Tandem 25,000 lbs. each
- Suspension Heavy duty hutch / leaf spring
- Brakes Full Air w/ABS Brake system
- Grounding Mounted front and rear Lugs
- Wheel Chocks 2 each with storage brackets
- Tie Downs Front & Rear frame mounted
- Hyd. Tank 70 gallons

OPTIONS AVAILABLE

- Vandalism package



MODEL T-5DP-120 SPECIFICATIONS

UNIT PERFORMANCE (Standard Pulling Drum)

- Continuous Torque Rating 120,000 in. lbs.
 - Line Speed (average) 4 mph
 - Full Drum Line Pull Rating 4,000 lbs.
- The above figures are for a single drum pulling. Levelwind provided is setup for pulling one drum at a time.*

ROPE-PULLING DRUM (QUANTITY 5)

- Diameter (O.D.) 60"
- Inside Width 40"
- Core Diameter 24"
- Approx. Line Capacity 22,000 ft. of 3/8" AMSTEEL BLUE

DIMENSIONS & WEIGHT (Standard Pulling Reel)

- Unit Length 42'6"
- Unit Width 8'
- Unit Height 11'7"
- Unit Net Weight 39,080 lbs.
- GVWR 56,000 lbs.
- GAWR 45,400 lbs.
- Tongue Weight 22,000 lbs.

COMBO OPTION: STEEL QTY 3 & UNITREX QTY2

- GVWR 63,000 lbs.
- GAWR 39,500 lbs.
- Tongue Weight 23,500 lbs.
- Approx. Line Capacity (3) Inbound Reels: 22,000' of 3/8" AMSTEEL BLUE
(2) Outboard Reels: 22,000 ft. of 3/8" Steel Rope