



The Wagner-Smith Equipment Co. **Model T-BWT-10-60** is a trailer mounted 60 in. diameter single conductor bullwheel tensioner. The bullwheels are canted to minimize line twisting. Maximum line tension rating is 10,000 lbs. and an average 4 mph line speed. This is a great unit for Transmission jobs.

OPERATING FEATURES

- Bullwheel brakes are smooth running hydraulic calipers.
- All unit operating controls are located at the operator's station, off the ground, for operator safety.
- Large diameter fairlead roller assembly is provided to reduce bending radius on input side.



MODEL T-BWT-10-60 SPECIFICATIONS

STANDARD FEATURES

- | | |
|--------------------|-----------------------------------|
| • Tension Brakes | Hydraulic actuated caliper/48 in. |
| • Dia. Front Hitch | Adjustable 3" lunette eye |
| • Lighting | DOT regulation (LED) |
| • Electrical Plug | 6-way pin |
| • Front Jack | Manual crank type |
| • Rear Jacks | Manual pin type |
| • Tires | 215/75R17.5 Load Range "H" |
| • Axle(s) | Tandem 8,000 lb. each |
| • Suspension | Leaf spring |
| • Brakes | Electric with breakaway switch |
| • Wheel Chocks | 2 each with support brackets |
| • Tie Downs | Front and rear on frame support |

UNIT PERFORMANCE

- | | |
|--------------------------|-------------|
| • Maximum Tension Rating | 10,000 lbs. |
| • Line Speed (Average) | 4 mph |

BULLWHEEL TENSIONER

- | | |
|------------------------|----------------------------------|
| • Diameter | 60" (bottom of groove) |
| • Groove Diameter | 2 1/8 in. |
| • Number of Grooves | 5 |
| • Replaceable Segments | Yes |
| • Bullwheel Lining | Elastomer (bolt-on) |
| • Tensioning Brakes | Hydraulic actuated caliper/ disc |
| • Brake discs | 48" diameter |

DIMENSIONS & WEIGHT

- | | |
|---------------|-------------|
| • Unit Length | 20' |
| • Unit Width | 8' |
| • Unit Height | 9'11" |
| • Net weight | 9,280 lbs. |
| • GVWR | 18,800 lbs. |
| • GAWR | 16,000 lbs. |
| • Tongue Load | 2,700 lbs. |

OPTIONS AVAILABLE

- 3 Groove elastomeric pads available