



A trailer mounted single reel carrier-tensioner; the Wagner-Smith Equipment Co. Model **T-BWT-3-31-RC** can be used in a wide range of Distribution stringing and tensioning applications.

OPERATING FEATURES

- The reel and spindle assembly lifts straight out of the machine without having to shift to the side. No tools required for reel removal.
- Corrosion resistant steel brake discs are standard for smooth operation and low maintenance.
- All unit operating controls are located at the operator's station, off the ground, for operator safety.
- A fairlead roller assembly is provided as standard between bullwheel and reel.
- Designed with canted bullwheels to reduce twist on conductor.

STANDARD FEATURES

- Tension Brakes Hydraulically actuated caliper/20" diameter
- Reel Brakes Hydraulically actuated caliper/20" diameter
- Front Hitch Adjustable 3" lunette eye
- Lighting DOT regulation (LED)
- Electrical Plug 6-way pin
- Front Jack Manual crank type
- Rear Jack Manual pin type
- Tires 235/75R17.5 Load Range "H"
- Axle Single 10,000 Lb. capacity
- Suspension Leaf spring
- Brakes Electric w/ breakaway switch
- Tie Downs Front and rear frame mounted
- Grounding Front and rear attached
- Wheel Chocks 2 each with support brackets

OPTIONS AVAILABLE

- Manual reel rewind complete with hand crank
- Hydraulic reel rewind motor & hoses
- Multiple reel carrier (stands)
- Rear crank jacks



MODEL T-BWT-3-31-RC SPECIFICATIONS

UNIT PERFORMANCE

- Maximum Tension Rating 3,000 lbs.
- Line Speed 4 mph

BULLWHEEL TENSIONER

- Diameter 31" (bottom of groove)
- Groove Diameter 1.50"
- Number of Grooves 5
- Replaceable Segments Yes
- Bullwheel Lining Elastomer (bolt-on)

REEL CARRIER

- Quantity One (1)
- Max. Reel Diameter 84"
- Max. Reel Width 48"
- Max. Reel Weight 6,200 lbs.
- Spindle Diameter 2 3/4" complete w/locking collars

DIMENSIONS & WEIGHT

- Unit Length 16'10"
- Unit Width 8"
- Unit Height 8'5"
- Net weight 4,700 lbs.
- GVWR 11,000 lbs.
- GAWR 10,000 lbs.
- Tongue Weight 1,580 lbs.