



- Quick change type reel and spindle assemblies lift straight out of the unit without having to shift to the side. No tools are required for reel removal.
- All unit operating controls are located at the operator's station, off the ground, for operator safety.
- A fairlead roller assembly is provided as standard.
- Designed with canted bullwheels to reduce twist on conductor.
- Corrosion resistant steel brakes discs are standard for smooth operation and low maintenance.

STANDARD FEATURES

- | | |
|-------------------|--|
| • Tension Brakes | Hydraulic actuated caliper/28 in. diameter |
| • Reel Brakes | Hydraulic actuated caliper/20 in. diameter |
| • Front Hitch | Adjustable 3" lunette eye |
| • Lighting | DOT regulation (LED) |
| • Electrical Plug | 6-way pin |
| • Front Jack | Manual crank type |
| • Rear Jacks | Manual pin type |
| • Tires | 215/75R17.5 Load Range "H" |
| • Axle(s) | Tandem 8,000 lb. each |
| • Suspension | Leaf spring |
| • Brakes | Electric with breakaway switch |
| • Grounding Lugs | Mounted front and rear |
| • Wheel Chocks | 2 each with support brackets |
| • Tie Downs | Front and rear frame mounted |

OPTIONS AVAILABLE

- 2 3/4 to 5 1/4 Standard Reel Arbor Adapters
- Rear jacks with manual crank type
- Multiple reel carrier (stands)
- Manual reel rewind complete with crank
- Hydraulic reel rewind motor & hoses
- Rear crank jacks
- Capstan with Hydraulic / Engine package

MODEL T-BWT-4-38-RC SPECIFICATIONS

UNIT PERFORMANCE

- | | |
|--------------------------|------------|
| • Maximum Tension Rating | 4,000 lbs. |
| • Line Speed | 4 mph |

BULLWHEEL TENSIONER

- | | |
|------------------------|------------------------|
| • Diameter | 37" (bottom of groove) |
| • Groove Diameter | 1.50" |
| • Number of Grooves | 5 |
| • Replaceable Segments | Yes |
| • Bullwheel Lining | Elastomer (bolt-on) |

REEL CARRIER

- | | |
|----------------------|-----------------------------------|
| • Quantity | One (1) |
| • Max. Reel Diameter | 90" |
| • Max. Reel Width | 56" |
| • Max. Reel Weight | 10,000 lbs. |
| • Spindle Diameter | 2 3/4" complete w/locking collars |

DIMENSIONS & WEIGHT

- | | |
|-----------------|-------------|
| • Unit Length | 19' |
| • Unit Width | 8' |
| • Unit Height | 9'4" |
| • Net weight | 5,820 lbs. |
| • GVWR | 17,600 lbs. |
| • GAWR | 16,000 lbs. |
| • Tongue Weight | 2,200 lbs. |