

T-RC-96X54-12

A trailer mounted, one place reel carrier, the Wagner-Smith Equipment Co. *Model T-RC-96x54-12* is designed to transport and tension cable or conductor reels up to 96" in diameter, 54" wide, and weighing up to 12,000 pounds per reel.

OPERATING FEATURES

- Quick change type reel and spindle assemblies lift straight out of the unit without having to shift to the side. No tools are required for reel removal.
- Reel spindles may incorporate an <u>optional</u> mechanical manual rewind to allow the operator to rewind conductor via a hand crank or external hydraulic supply when job is completed.



Front Hitch Adjustable 3" lunette eyeLighting DOT regulation (LED)

• Electrical Plug 6-way pin

Front Jack Manual crank typeRear Jacks Manual pin type

• Tires 215/75R17.5 Load Range "H"

• Axle (s) Tandem 8,000 lb. each

Suspension Slipper spring

• Brakes Electric with breakaway switch

Grounding Lugs
 Wheel Chocks
 Tie Downs
 Mounted front and rear
 Wheel chocks with holders
 Front and rear frame mounted

Brake Disc ASTM 588 steel

OPTIONS

• Mechanical manual rewind

• Hydraulic drive motor assembly

• Powered rewind assembly



MODEL T-RC-96X54-12 SPECIFICATIONS

UNIT PERFORMANCE - REEL CARRIER

Quantity One (1)
Max. Reel Diameter 96"
Max. Reel Width 54"

Max. Reel Weight 12,000 lbs. (each)
 Spindle Diameter 2³/₄" w/ locking collars

Reel Brakes Hydraulically actuated caliper

20 inch diameter disc

 Reel Loading Quick change type without altering reel brake adjustment.

DIMENSIONS & WEIGHT:

Unit Length
 Unit Width
 Unit Height
 Net Weight
 GVWR
 GAWR
 Tongue Weight (empty)
 16'5"
 3'
 7'9"
 16,400 lbs.
 360 lbs.









