



## OPERATING FEATURES

- Easy, one-person operation
- Quick change type reel and spindle assemblies lift straight out without having to shift to the side.  
\*No tools required\*
- No-hassle maintenance
- Versatility in size of spool
- Designed with low center of gravity
- All hose and wiring protected within frame
- Engineered for optimum performance and safety



## MODEL T-URC-120X60 BASIC SPECIFICATIONS

### STANDARD FEATURES

- |                   |   |
|-------------------|---|
| • Front Hitch     | Adjustable 3" lunette eye                           |
| • Lighting        | DOT regulation                                      |
| • Electrical Plug | 6-way pin   |
| • Front Jack      | Manual crank type                                   |
| • Tires           | 235/75R17.5   |
| • Axle (s)        | Stub axles  |
| • Brakes          | Electric with wet cell battery and breakaway switch |
| • Wheel Chocks    | Wheel chocks with holders                           |
| • Reel Lift       | Manual Hydraulics                                   |

### UNIT PERFORMANCE - REEL CARRIER

- |                          |                   |
|--------------------------|-------------------|
| • Reel Quantity          | One (1)           |
| • Max. Reel Diameter     | 120"              |
| • Max. Reel Width        | 60"               |
| • Trailer Payload Rating | 7,020 lbs.        |
| • Spindle Diameter       | 2-1/2"            |
| • Reel Loading           | Quick change type |

### DIMENSIONS & WEIGHT

- |               |            |
|---------------|------------|
| • Unit Length | 10'10"     |
| • Unit Width  | 8'         |
| • Net Weight  | 1,480 lbs. |
| • GVWR        | 8,500 lbs. |