GMP SIDEWINDER

THE RIGHT EQUIPMENT FOR ALL OF YOUR TELECOMMUNICATIONS NEEDS.



Co

1/5

Equipment





The GMP SideWinder Trailer-Mounted Fiber Optic Puller SideWinder Fiber Optic Puller has been designed to exceed the requirements of installing underground telecommunication cables, high-density fiber by employing a 42 in. diameter single capstan to provide a controlled force to the pulling rope or tape.

The single capstan allows the winch to be placed at the midpoint of a section to assist in the pull, thus enabling longer pulls to be achieved.

FEATURES

CAPSTAN ANGLED AT 30 DEGREES

USER FRIENDLY CONTROLS

ELECTRIC START ENGINE

QUICK DISCONNECT HYDRAULICS





GMP SIDEWINDER SPECIFICATIONS

STANDARD FEATURES	
Axle	Single
Engine	13 hp Honda GX390
Tires	205/75D14
Lighting	DOT approved
Electrical	7 way RV blade type
Gear Box	Inline capstan drive
Hydraulic Oil	16.5 gal tank capacity
Track	60"
UNIT PERFORMANCE	
Max. Pulling Capacity	600 lbs.
Capstan Diameter	42"
(Avg.) Line Speed	200 ft/min.
Drum Capacity	4000' 1/4" Polyrope
DIMENSIONS & WEIGHT	
LXWXH	123" x 69" x 57"
GVWR	1,500 lbs.

EQUIPPED LOCATIONS NATIONWIDE

All equipment is available for purchase and rental through our five locations across the USA. We want to be prepared for all of your demands because we are dedicated to helping the industry whenever you need it.

Ð


 \bigcirc

(in)



*Wagner-Smith Equipment Co. reserves the right to change the specification of any unit at any time without prior notice. This spec sheet is only a statement of general specifications on the date of this publication.





Þ



REV. 2023