



**TRANSPORTATION AND CLEANUP ALL WITHIN ONE
PIECE OF EQUIPMENT.**



**THIS UTILITY TRAILER IS DESIGNED
FOR VARIOUS LENGTHS OF POLES.**

This trailer is your all in one need for transporting poles and reels. With up to 60" reel capacity and a variety length of poles, you have the most versatile piece of equipment. Also capable of hauling out debris and waste from the job site.



FEATURES

TELESCOPING FRAME

ADJUSTABLE REAR
BOLSTERS FOR BALANCE

EQUIPPED CARGO
STRAPS

50014-12R

MPT-14 TRAILER SPECIFICATIONS

STANDARD FEATURES	
Hitch	Adjustable 3" lunette eye
Electrical	6 way pole plug with spring cable protector
Lighting	DOT approved
Jack	Manual front crank
Tires	9.5 x 16.5 Load Range "E"
Axles	Dual
Suspension	Slipper spring
Brakes	Electric
Straps	4
Strap Width	4"
Towing	1/2" chain
Wheel Chocks	Equipped
Tie Downs/Grounding	Front and rear mounted
REEL CAPACITY	
Max. Reel Diameter	60"
Max Reel Width	55"
DIMENSIONS & WEIGHT	
Length Retracted	27'2"
Length Extended	37'2"
Width	7'8"
Height	5'10"
Height w/Reel	7'8"
Bolster Height	18 1/4"
GAWR	12,780 lbs.
GVWR	16,000 lbs.
Empty Trailer Weight	4,360 lbs.
Cargo Capacity (Poles)	12,000 lbs.
Cargo Capacity (Reel)	10,000 lbs.
Tongue Weight (Empty)	620 lbs.

EQUIPPED LOCATIONS NATIONWIDE

All equipment is available for purchase and rental through our five locations across the USA. We want to be prepared for all of your demands because we are dedicated to helping the industry whenever you need it.

ASSEMBLED IN THE USA

All Wagner-Smith Equipment Co. equipment are assembled in our state-of-the-art facilities in Lawrenceville, IL and Burleson, TX. Replacement parts are quickly fulfilled from our Burleson, TX location and shipped to anywhere in North America.

*Wagner-Smith Equipment Co. reserves the right to change the specification of any unit at any time without prior notice. This spec sheet is only a statement of general specifications on the date of this publication.

To learn more or find a location nearest you,
please visit **WagnerSmith.com**



**Wagner
Smith**
Equipment Co.

50014-12R

REV. 2023

