


POWER UP THOSE UNITS WITH A LITTLE EXTRA HORSEPOWER.





PERFECT FOR ADDITIONAL POWER.

system with variable flow control and a mobile frame designed to be used with many equipment applications, including our reel stands, capstan reels, hydraulic tools up to 13 gpm and 2,150 psi.









FLAT FACE DISCONNECTS

LIFTING MADE EASY WITH

VARIABLE FLOW CONTROLS





POWER PACK SPECIFICATIONS

STANDARD FEATURES	
Hydraulic System	13 GPM @ 2,150 psi w/variable flow control
Engine	18 hp Briggs & Stratton
Hydraulic Pump	14.4 cc Danfoss gear pump
Hydraulic Tank	20 gallon
Fuel	2.25 gallon gas tank
Lifting	1" lifting eye
DIMENSIONS & WEIGHT	
LXWXH	3'6" x 2'9" x 2'11"
Weight	700 lbs.
Centerpoint	2'
Forklift Opening Height	2 5/8"
Forklift Opening Width	5 5/8"



EQUIPPED LOCATIONS NATIONWIDE

All equipment is available for purchase and rental through our five locations across the USA. We want to be prepared for all of your demands because we are dedicated to helping the industry whenever you need it.

ASSEMBLED IN THE USA

All Wagner-Smith Equipment Co. equipment are assembled in our state-of-the-art facilities in Lawrenceville, IL and Burleson, TX. Replacement parts are quickly fulfilled from our Burleson, TX location and shipped to anywhere in North America.

*Wagner-Smith Equipment Co. reserves the right to change the specification of any unit at any time without prior notice. This spec sheet is only a statement of general specifications on the date of this publication.



To learn more or find a location nearest you, please visit **WagnerSmith.com**











48018-01R