


THIS SMALL BUT MIGHTY, FOUR DRUM PULLER IS USED IN A WIDE RANGE OF STRINGING APPLICATIONS.



FEATURES DISC/HYDRAULIC CALIPER APPLICATION FOR BRAKING.

This small, but powerful, portable four reel puller can be mounted to any pole or placed on the ground.







STANDARD LEAD SCREW LEVEL WIND

VERSATILITY FOR WIDE RANGE OF APPLICATIONS

41014-2DR

SPM-4DP-13.5 SPECIFICATIONS

STANDARD FEATURES	
Brake Type	Manual caliper on drag brakes
Drum Clutch	Individual
Air	Auxiliary Hydraulic System Needed
REEL CAPACITY	
3/8" Rope	6,000'
Quantity	4
Inside Width	23"
Diameter	27"
Core Diameter	10 3/4"
DIMENSIONS & WEIGHT	
LXWXH	66" x 76" x 49"
Net Weight	2,200 lbs.
Weight with 3/8" Rope	3,136 lbs.
UNIT PERFORMANCE - EMPTY DRUM *(Based on 20 gpm @ 2,000 psi)	
Rated Line Pull	2,200 lbs.
Max Line Pull @ 3,000 psi	3,300 lbs.
Line Speed*	0-312 ft/min.
Line Speed Average	543 ft/min.
UNIT PERFORMANCE - FULL DRUM *(Based on 20 gpm @ 2,000 psi)	
Rated Line Pull	880 lbs.
Max Line Pull @ 3,000 psi	1,300 lbs.
Line Speed*	0-775 ft/min.
Line Speed Average	543 ft/min.



EQUIPPED LOCATIONS NATIONWIDE

All equipment is available for purchase and rental through our five locations across the USA. We want to be prepared for all of your demands because we are dedicated to helping the industry whenever you need it.

ASSEMBLED IN THE USA

All Wagner-Smith Equipment Co. equipment are assembled in our state-of-the-art facilities in Lawrenceville, IL and Burleson, TX. Replacement parts are quickly fulfilled from our Burleson, TX location and shipped to anywhere in North America.

*Wagner-Smith Equipment Co. reserves the right to change the specification of any unit at any time without prior notice. This spec sheet is only a statement of general specifications on the date of this publication.



To learn more or find a location nearest you, please visit **WagnerSmith.com**





