

SINGLE DRUM PULLING JUST GOT SOME MUSCLE BUILT INTO IT.





SAFETY CONTROLLED BY SPRING APPLIED HYDRAULIC PRESSURE

The Model T-1DP-1140-FT4 can be preset for the desired pulling.

All unit operating controls are located at the operator's station, off the ground, for the operator's safety.

The following are included as standard features: steel pulling drum, hydraulic levelwind assembly, free-wheeling brake safety guard, operator's safety screen and adjustable seat. This is a custom program created exclusively for WSE to communicate with FT4 engines and provide a better operating experience for the user.

STEEL PULLING DRUM WITH HYDRAULIC LEVELWIND

OFF THE GROUND OPERATIONS

USED FOR WIDE RANGE OF TRANSMISSION JOBS

401140-11R

T-1DP-1140-FT4 SPECIFICATIONS

STANDARD FEATURES	
Levelwind	Hydraulically driven and operated rail with removable top roller
Engine	400 HP FT4 diesel
Front Hitch	2" Kingpin fifth wheel
Lighting	DOT Regulation LED
Electrical	7 way socket
Grounding Lugs	Front & Rear mounted
Jacks	Hydraulically driven
Tires	285/75R24.5 Load range "G"
Suspension	Slipper leaf spring
Trailer Brakes	Full air w/ABS brakes system
Wheel Chocks	Provided
Freewheeling	(2) 82" band brakes with 3 3/4" wide lining
Drive Clutches	Hydraulic disengagement
Hydraulic Tank	150 gallons
Axles	Tri with 27,500 lbs. capacity per axle
UNIT PERFORMANCE	
Continuous Torque Rating	1,140,000 in. lbs.
Line Speed Average	4 mph.
Full Drum Line Pull Rating	30,000 lbs.
STANDARD PULLING REEL	
Diameter	81"
Inside Width	50"
Core Diameter	42"
Approximate Line Capacity	25,000 3/4" wire rope
DIMENSIONS & WEIGHT	
LXWXH	48' x 8' x 13'2"
Net Weight without Rope	60,510 lbs.
GVWR	99,700 lbs.
GAWR	60,000 lbs.
Tongue Weight	36,020 lbs.



EQUIPPED LOCATIONS NATIONWIDE

All equipment is available for purchase and rental through our five locations across the USA. We want to be prepared for all of your demands because we are dedicated to helping the industry whenever you need it.

ASSEMBLED IN THE USA

All Wagner-Smith Equipment Co. equipment are assembled in our state-of-the-art facilities in Lawrenceville, IL and Burleson, TX. Replacement parts are quickly fulfilled from our Burleson, TX location and shipped to anywhere in North America.

*Wagner-Smith Equipment Co. reserves the right to change the specification of any unit at any time without prior notice. This spec sheet is only a statement of general specifications on the date of this publication.



To learn more or find a location nearest you, please visit **WagnerSmith.com**

401140-11R









