

TRAILER MOUNTED HEAVY DUTY PULLER FOR TRANSMISSION STRINGING APPLICATIONS.



HEAVY DUTY STRINGING PULLER FOR THOSE MULTIPLE PULLS

The internal pressure compensated closed-loop hydraulic system minimizes heat build up of hydraulic fluid and can preset desired pulling pressure. A spring applied, hydraulic pressure released safety brake is standard in the main drive line for operator safety.



All unit operating controls are located at the operators station, off the ground, for operator safety. Touchscreen display/ electronics package — Now logs pull data, limits customer from damaging equipment because of "over limit" function. User can now see engine alerts and more detailed system alerts.



HYDRAULIC BRAKED BULLWHEEL

"HAUL BACK" PULL IN MODE

ONE, TWO OR THREE CONDUCTORS SIMULTANEOUSLY

41300-10R

T-3DP-300-FT4 SPECIFICATIONS

STANDARD FEATURES	
Levelwind	Hydraulically operated post type with swing out top roller
Engine	173 HP FT4
Front Hitch	Fifth wheel
Lighting	DOT regulation LED
Diesel	35 gallon
Jacks	Hydraulically operated
Hydraulic	100 gallon
Suspension	Heavy duty hutch/leaf spring
Tie Downs	3 1/2" ID Tie down ears at each corner
Grounding	Mounted front and rear lugs
Brakes	Full air ABS brake system
Wheel Chocks	Standard
UNIT PERFORMANCE	
Maximum Tension Rating	300,000 lbs.
Line Speed	4 mph.
Full Drum Line Pull Rating	10,000 lbs.
STANDARD PULLING DRUM	
Quantity	3
Diameter	58"
Inside Width	48"
Core Diameter	32"
Maximum Line Capacity	25,000 of 1/2" steel rope
DIMENSIONS & WEIGHT	
LXWXH	35'8" x 8' x 13'6"
Unit Weight Empty	41,900 lbs.
GVWR	82,900 lbs.
GAWR	60,000 lbs.
Tongue Weight	31,003 lbs. (Full drum wire rope)



EQUIPPED LOCATIONS NATIONWIDE

All equipment is available for purchase and rental through our five locations across the USA. We want to be prepared for all of your demands because we are dedicated to helping the industry whenever you need it.

ASSEMBLED IN THE USA

All Wagner-Smith Equipment Co. equipment are assembled in our state-of-the-art facilities in Lawrenceville, IL and Burleson, TX. Replacement parts are quickly fulfilled from our Burleson, TX location and shipped to anywhere in North America.

*Wagner-Smith Equipment Co. reserves the right to change the specification of any unit at any time without prior notice. This spec sheet is only a statement of general specifications on the date of this publication.



To learn more or find a location nearest you, please visit **WagnerSmith.com**

41300-10R









