



The T-3RC-90x52-30 is a three-place reel carrier used for underground work. Designed to transport and payout fiber optic and innerduct reels up to 90" diameter, 52" wide, and weighing up to 10,000 lbs. per reel. The adjustable fairlead design allows all reels to operate at the same time, maximizing productivity on this underground reel carrier.

Key Features

- Reel spindles are designed for quick change and require no hand tools
- Provides flexible handling of multiple spool sizes for added versatility
- Fairlead allows all reels to be used simultaneously
- Enables fast, tool-free reel changes by simply opening two flip-open bearing caps and lifting the spindle straight up

Unit Performance	
Payload Rating	10,000 lbs.
Reel Capacity	Three
Reel Lift	Quick lift, no tools required
Reel Specs	
Max. Diameter	90"
Max. Width	52"
Spindle Diameter	2 3/4" with locking collar
Reel Loading	Quick change
Towing	
Lighting	DOT Regulated LED
Electrical Plug	6 way pin
Jacks	Front manual crank
Axles	Tridem 12,000 lb. capacity each
Trailer Brakes	Electric with battery & breakaway switch
Front Hitch	Adjustable 3" lunette eye
Suspension	Slipper leaf spring

Dimensions & Weight	
L X W X H	32'2" x 8' x 9'4" (fairlead retracted); 12'8" (fairlead extended)
Unit Weight	6,460 lbs.
GVWR	38,886 lbs.
GAWR	34,000 lbs.
Tongue Weight	600 lbs.

Built for Telecom & Fiber Installation Crews

- Do more with one trailer- run three reels without the need for additional equipment
- Simplify your jobsite setup



Rental Item #: **47090-14R**

For additional details on the T-3RC-90x52-30, view the operator's [manual](#).