



Built for transmission and heavy distribution work, the T-4DP-130-FT4 balances power, control, and multi-line efficiency. Designed to keep crews productive while maintaining accurate tension across all reels. Provides full pull visibility and data logging.

Key Features

- Four independently operated drums with mechanical clutches
- Mechanical fly overspin brakes for freewheeling payout
- Pressure-compensated closed-loop hydraulic system
- Variable-pressure hydrostatic drive
- Hydraulic overspin brakes for controlled payout
- Electronic display showing line pull, line speed, and reel diameter

Unit Performance	
Line Speed	5.5 MPH
Synthetic Rope 5/8" X 16,500'	Full Drum Pull Rating - 3,700 lbs.
Dyneema® Rope 7/16" X 22,000'	Full Drum Pull Rating - 4,100 lbs.
Standard Features	
Number of Reels	4
Drum Diameter	64"
Drum Inside Width	22"
Drum Core Diameter	20"
Engine	115 HP FT4
Freewheel - Braking	35" disc - hydraulic
Trailer Braking System	Air ABS brake system
Hydraulic Tank Capacity	40 gallon
Levelwind System	Hydraulically operated post type with swing out top roller
Drum	4 independent manual on reels
Fuel Capacity	19 gallon diesel

Towing	
Suspension	Heavy duty hutch/leaf spring
Configuration / Axle Rating	Tandem 22,500 lbs.
Front Hitch	Adjustable 3" lunette eye
Jacks	Front manual crank/rear pin
Trailer Electrical Connection	7 way pin
Grounding	Front/rear mounted lugs
Lighting	DOT regulation LED
Tie Downs	On each corner
Dimensions & Weight	
Overall Dimensions (L x W x H)	24' 6.5" x 8' x 12' 5.5" (10'6.5" in transport mode)
Net Weight (empty)	22,280 lbs.
GAWR	34,000 lbs.
GVWR	36,717 lbs.
Tongue Weight	2,832 lbs. (Full drum with rope)

Rental Item #: **41130-11R**

For additional details on the T-4DP-130-FT4, view the operator's [manual](#).