



FEATURES

TOUCH SCREEN
OPERATING PANEL

UP TO 22,000' LINE
CAPACITIES

USED IN A RANGE
OF TRANSMISSION
APPLICATIONS

SMALL, COMPACT, HIGH PERFORMANCE PULLER THAT IS ECONOMICAL AND VERSATILE.

PULLING OPERATIONS ALL DONE AT THE OPERATORS STAND FOR SAFETY.

Both simple to operate and easy to maintain, the T-4DP-130-FT4 is another innovative product designed and developed to meet the changing needs of the power line construction industry..



**APPROXIMATE
LINE CAPACITY**

16,500' 5/8" Synthetic Rope
22,000' 3/8" Amsteel Blue
22,000' 7/16" Amsteel Blue

41130-11R

T-4DP-130-FT4 SPECIFICATIONS

STANDARD FEATURES	
Diesel Engine	115HP FT4
Fuel Tank	19 gallons
Hydraulic Tank	40 gallons
Levelwind	Post type with swing top roller, hydraulically operated
Front Hitch	Adjustable 3" lunette eye
Electrical Connection	7 pole plug with spring cable
Suspension	2 supplied on mounting tubes
Lighting	D.O.T. regulation LED
Tires	255/70R22.5 with Load rating of "H"
Axles	Tandem 22,500 lbs. each
Suspension	Slipper leaf spring
Brakes	Air with ABS front axle
Jacks	Front and Rear
Wheel Chocks	Supplied
Tie Downs	3 1/2" ID Ears
UNIT PERFORMANCE <i>(figures for a single drum pulling. Levelwind designed for pulling with one drum at a time)</i>	
Line Speed (average)	5.5 mph.
Actual Full Drum Pull Rating	3,700 lbs. 5/8" synthetic rope
	4,100 lbs. 7/16" Amsteel Blue
	3,920 lbs. 3/8" Amsteel Blue
STANDARD PULLING REEL	
Reel	4
Diameter	64"
Inside Width	22"
Core Diameter	20"
Approximate Line Capacity	16,500' 5/8" Synthetic Rope
	22,000 3/8" Amsteel Blue
	22,000 7/16" Amsteel Blue
DIMENSIONS & WEIGHT	
L X W X H	24'6.5" x 8' x 12'5.5" <i>(when operated)</i> 10'6.5" <i>(when transported)</i>
Net Weight without Rope	22,820 lbs.
GVWR	36,717 lbs.
GAWR	34,000 lbs.
Tongue Weight	2,832 lbs.



EQUIPPED LOCATIONS NATIONWIDE

All equipment is available for purchase and rental through our five locations across the USA. We want to be prepared for all of your demands because we are dedicated to helping the industry whenever you need it.

ASSEMBLED IN THE USA

All Wagner-Smith Equipment Co. equipment are assembled in our state-of-the-art facilities in Lawrenceville, IL and Burleson, TX. Replacement parts are quickly fulfilled from our Burleson, TX location and shipped to anywhere in North America.

*Wagner-Smith Equipment Co. reserves the right to change the specification of any unit at any time without prior notice. This spec sheet is only a statement of general specifications on the date of this publication.

To learn more or find a location nearest you, please visit **WagnerSmith.com**



**Wagner
Smith**
Equipment Co.

41130-11R

REV. 2023