



The Wagner-Smith T-4DP-200-FT4 combines four-drum versatility with powerful, precise tension for transmission applications, featuring independent clutches, hydraulic overspin brakes, and real-time pull data monitoring with integrated data logging. This machine maintains consistent tension and performance across multiple conductors.

Key Features

- Four independently clutched pulling drums
- Hydraulic overspin fly out brakes for controlled payout with or without engine running
- Hydrostatic system with variable pressure and electronic controls
- Real-time electronic display showing line pull, line speed, and reel diameter alongside pull data storage

Unit Performance	
Line Speed	4 MPH
Dyneema® - 9/16" X 26,000"	Full Drum Pull Rating - 6,000 lbs.
Standard Features	
Number of Reels	4
Drum Diameter	62"
Drum Inside Width	48"
Drum Core Diameter	32"
Engine	140 HP FT4
Freewheel - Braking	42" Disc - Hydraulic
Trailer Braking System	Air ABS brake system
Hydraulic Tank Capacity	100 gallon
Levelwind System	Hydraulically operated post type with swing out top roller
Drive Clutches	Jaws on drives
Fuel Capacity	35 gallon diesel

Towing	
Configuration / Axle Rating	Heavy duty hutch/leaf spring
Front Hitch	Fifth wheel
Jacks	Hydraulically operated
Trailer Electrical Connection	7 way socket
Grounding	Front/Rear mounted lugs
Lighting	DOT regulation LED
Tie Downs	Qty (2) - 2 1/4" ID front
Dimensions & Weight	
Overall Dimensions (L x W x H)	40' x 8' x 13'6"
Net Weight (empty)	42,880 lbs.
GAWR	34,000 lbs.
GVWR	59,200 lbs.
Tongue Weight	25,800 lbs. (Full drum wire rope)

The T-4DP-200-FT4 is offered solely as a purchase-only unit; it is not offered in the rental line-up.

For additional details on the T-4DP-200-FT4, view the operator's [manual](#).