



TRAILER MOUNTED PULLER USED FOR TRANSMISSION AND STRINGING APPLICATIONS.

HEAVY DUTY MULTIPLE DRUM PULLER

Internally pressure compensated closed-loop hydraulic system, minimizes heat build up of hydraulic fluid, can preset desired pulling pressure. Spring applied, hydraulic pressure released safety brake is standard in the main drive line for operator safety.

All unit operating controls are located at the operator's station, off the ground, for operator safety. Fold down safety screen and seat are all included as standard features.

Each drum can be disconnected for free wheeling with brake over spin control. Hydraulic pressure control, drum speed control and gauges are panel mounted.

FEATURES

ALL OPERATIONS AT THE CONTROL PANEL

CLOSED LOOP HYDRAULIC SYSTEM

LEVELWIND PROVIDED FOR SINGLE DRUM PULLING

41200-12

T-4DP-200-FT4 SPECIFICATIONS

| STANDARD FEATURES | |
|--|---|
| Levelwind | Hydraulic post type with swing top roller, hydraulically operated |
| Engine | 140 HP FT4 |
| Front Hitch | Fifth wheel |
| Lighting | DOT regulation LED |
| Electrical Plug | 7 way pin |
| Front Jack | Hydraulically operated |
| Tires | 455/55R22.5 Load range "L" |
| Axles | Tandem 22,500 lbs. each |
| Suspension | Heavy duty hutch/leaf spring |
| Brakes | Full air ABS brake system |
| Fuel Tank | 35 gallon diesel |
| Hydraulic Tank | 100 gallon |
| Wheel Chocks | Standard |
| Brake Disc | 42" |
| Grounding | Front/Rear mounted lugs |
| UNIT PERFORMANCE (STANDARD PULLING REEL) | |
| Continuous Torque Rating | 200,000 in. lbs. |
| Line Speed Average | 4 mph. |
| Full Drum Line Pull Rating | 6,800 lbs. |
| FIBER ROPE PULLING DRUM | |
| Quantities | 4 |
| Diameter | 62" |
| Inside Width | 48" |
| Core Diameter | 32" |
| Approximate Line Capacity | 25,000' 1/2" Dyneema rope |
| DIMENSIONS & WEIGHT | |
| L X W X H | 40' x 8' x 13'6" |
| Approximate Net Weight | 40,000 lbs. |
| GVWR | 65,000 lbs. |
| GAWR | 34,000 lbs. |

EQUIPPED LOCATIONS NATIONWIDE

All equipment is available for purchase and rental through our five locations across the USA. We want to be prepared for all of your demands because we are dedicated to helping the industry whenever you need it.

ASSEMBLED IN THE USA

All Wagner-Smith Equipment Co. equipment are assembled in our state-of-the-art facilities in Lawrenceville, IL and Burleson, TX. Replacement parts are quickly fulfilled from our Burleson, TX location and shipped to anywhere in North America.

*Wagner-Smith Equipment Co. reserves the right to change the specification of any unit at any time without prior notice. This spec sheet is only a statement of general specifications on the date of this publication.

To learn more or find a location nearest you, please visit **WagnerSmith.com**



**Wagner
Smith**
Equipment Co.

41200-12

REV. 2023