



The T-4DP-36-FT4 is engineered for efficient distribution line-stringing where multiple lines and tight schedules demand control. Independent drum operation and preset pulling force help crews work faster without sacrificing precision.

Key Features

- Four independently operated drums with mechanical clutches
- Mechanical fly overspin brakes for freewheeling payout
- Pressure-compensated closed-loop hydraulic system
- 36 hp water-cooled diesel engine
- Hydrostatic drive with variable pressure control
- Automatic diamond leadscrew levelwind for even rope winding

Unit Performance	
Line Speed	4 MPH
Synthetic Rope 1/2" X 8,000'	Full Drum Pull Rating - 3,125 lbs.
Standard Features	
Number of Reels	4
Drum Diameter	36"
Drum Inside Width	23"
Drum Core Diameter	10.75"
Engine	36 HP FT4
Freewheel - Braking	18" disc - mechanical control
Trailer Braking System	Electric with breakaway switch
Hydraulic Tank Capacity	30 gallon
Levelwind System	Automatic diamond lead screw
Drum	4 independent manual on reels
Fuel Capacity	19 gallon diesel

Towing	
Suspension	Slipper leaf spring
Configuration / Axle Rating	Single 10,000 lbs.
Front Hitch	Adjustable 3" lunette eye
Jacks	Front manual crank/rear pin
Trailer Electrical Connection	6 way pin
Grounding	Front/rear mounted lugs
Lighting	DOT regulation LED
Tie Downs	On each corner
Dimensions & Weight	
Overall Dimensions (L x W x H)	15'8" x 8' x 8'5"
Net Weight (empty)	7,280 lbs.
GAWR	9,610 lbs.
GVWR	10,800 lbs.
Tongue Weight	1,500 lbs. (Full drum with rope)

Rental Item #: **41036-15R**

For additional details on the T-4DP-36-FT4, view the operator's [manual](#).