

SMALL, COMPACT, HIGH PERFORMANCE PULLER THAT IS ECONOMICAL AND VERSATILE.



DISTIBLIFIED CONTINUE CONTINUE



PULLING OPERATIONS ALL DONE AT THE OPERATORS STAND FOR SAFETY.

This trailer mounted four drum puller is simple to operate and easy to maintain. This is yet another innovative product designed and engineered to meet the changing needs of the power line construction industry.

The integrated touch screen allows operators easy access to controls, system/usage data and equipment manuals.

UP TO 8,000' LINE CAPACITIES

CLOSED LOOP HYDRAULIC SYSTEM FOR MINIMIZED HEAT BUILD UP

APPROXIMATE LINE CAPACITY

8,000' 1/2" Synthetic Rope

41036-15R

T-4DP-36-FT4 SPECIFICATIONS

STANDARD FEATURES	
Diesel Engine	36HP FT4
Levelwind	Automatic diamond lead screw
Front Hitch	Adjustable 3" lunette eye
Drive Clutches	4 independent manual on reels
Grounding	Front and rear lugs
Jacks	Front manual crank/Rear pin
Wheel Chocks	2 supplied on mounting tubes
Lighting	D.O.T. regulation LED
Tires	215/75R17.5 with Load rating of "H"
Axles	Single 10,000 lbs. each
Suspension	Slipper leaf spring
Brakes	Electric with breakaway switch
UNIT PERFORMANCE	
Continuous Torque Rating	36,000 in. lbs.
Line Speed (average)	4 mph.
Actual Full Drum Pull Rating	2,000 lbs.
STANDARD PULLING REEL	
Reel	4
Diameter	36"
Inside Width	23"
Core Diameter	10.75"
Approximate Line Capacity	8,000′ 1/2″ synthetic rope
DIMENSIONS & WEIGHT	
LXWXH	15'8" x 8' x 8'5"
Net Weight without Rope	7,280 lbs.
GVWR	10,800 lbs.
GAWR	9,610 lbs.
Tongue Weight	1,500 lbs.



EQUIPPED LOCATIONS NATIONWIDE

All equipment is available for purchase and rental through our five locations across the USA. We want to be prepared for all of your demands because we are dedicated to helping the industry whenever you need it.

ASSEMBLED IN THE USA

All Wagner-Smith Equipment Co. equipment are assembled in our state-of-the-art facilities in Lawrenceville, IL and Burleson, TX. Replacement parts are quickly fulfilled from our Burleson, TX location and shipped to anywhere in North America.

*Wagner-Smith Equipment Co. reserves the right to change the specification of any unit at any time without prior notice. This spec sheet is only a statement of general specifications on the date of this publication.



To learn more or find a location nearest you, please visit WagnerSmith.com



41036-15R







