



The T-4DP-75-FT4 delivers four-drum versatility for distribution and light transmission work. The crossover designed for smooth operation and consistent tension, supports efficient multi-reel stringing with full pull visibility and data logging.

Key Features

- Four independently clutched pulling drums
- Mechanical fly overspin brakes for freewheeling payout
- Hydrostatic drive with variable pressure control
- Electronic display showing line pull, line speed, and reel diameter

Unit Performance	
Line Speed	4.5 MPH
Synthetic Rope 5/8" X 10,000'	Full Drum Pull Rating - 3,125 lbs.
Dyneema Rope 3/8" X 22,000'	Full Drum Pull Rating - 3,920 lbs.
Standard Features	
Number of Reels	4
Drum Diameter	48"
Drum Inside Width	25"
Drum Core Diameter	14"
Engine	74 HP FT4
Freewheel - Braking	12" drum - mechanical control
Trailer Braking System	Electric with breakaway switch
Hydraulic Tank Capacity	40 gallon
Levelwind System	Hydraulically operated post type with swing out top roller
Drum	4 independent manual on reels
Fuel Capacity	35 gallon diesel

Towing	
Suspension	Slipper leaf spring
Configuration / Axle Rating	Tandem 10,000 lbs. each
Front Hitch	Adjustable 3" lunette eye
Jacks	Front manual crank/rear pin
Trailer Electrical Connection	6 way pin
Grounding	Front/rear mounted lugs
Lighting	DOT regulation LED
Tie Downs	On each corner
Dimensions & Weight	
Overall Dimensions (L x W x H)	19'3" x 8' x 9'9" (8'4" in transport mode)
Net Weight (empty)	14,380 lbs.
GAWR	19,220 lbs.
GVWR	21,700 lbs.
Tongue Weight	2,500 lbs. (Full drum with rope)

Rental Item #: **41075-19R**

For additional details on the T-4DP-75-FT4, view the operator's [manual](#).