



### FEATURES

TOUCH SCREEN  
OPERATING PANEL

UP TO 22,000' LINE  
CAPACITIES

USE IN TRANSMISSION  
APPLICATIONS

### SIMPLE OPERATION WITH INNOVATIVE DESIGN TO MEET CHANGING NEEDS OF THE INDUSTRY.

#### USED IN A WIDE RANGE OF TRANSMISSION APPLICATIONS.

This trailer mounted four drum puller is simple to operate and easy to maintain. This is yet another innovative product designed and engineered to meet the changing needs of the power line construction industry.

The integrated touch screen allows operators easy access to controls, system/usage data and equipment manuals.



## 41075-19R

# T-4DP-75-FT4 SPECIFICATIONS

STANDARD FEATURES	
Diesel Engine	74HP FT4
Fuel Type	Diesel
Fuel Capacity	19 gallons
Hydraulic Reservoir	40 gallons
Levelwind	Two post type with swing out top roller, hydraulically operated
Front Hitch	Adjustable 3" lunette eye
Electrical Connection	6 way pin
Grounding	Front and rear lugs
Jacks	Front manual crank/Rear pin
Wheel Chocks	2 supplied on mounting tubes
Lighting	D.O.T. regulation LED
Tires	215/75R17.5 with Load rating of "H"
Axles	Tandem 10,000 lbs. each
Suspension	Slipper leaf spring
Brakes	Electric with breakaway switch
UNIT PERFORMANCE <i>(figures for a single drum pulling. Levelwind designed for pulling with one drum at a time)</i>	
Line Speed Average	4.5 mph.
Full Drum Line Rating	3,125 lbs. w/ 5/8" synthetic rope
	3,920 lbs. w/ 3/8" Amsteel Blue
STANDARD PULLING REEL	
Reel	4
Diameter	48"
Inside Width	25"
Core Diameter	14"
Approximate Line Capacity	10,000' 5/8" synthetic rope
	22,000' 3/8" Amsteel Blue
DIMENSIONS & WEIGHT	
L X W X H	19'3" x 8' x 9'4" <i>(when operated)</i> 8'4" <i>(when transported)</i>
Net Weight without Rope	14,380 lbs.
GVWR	21,700 lbs.
GAWR	19,220 lbs.
Tongue Weight	2,500 lbs.



## EQUIPPED LOCATIONS NATIONWIDE

All equipment is available for purchase and rental through our five locations across the USA. We want to be prepared for all of your demands because we are dedicated to helping the industry whenever you need it.

## ASSEMBLED IN THE USA

All Wagner-Smith Equipment Co. equipment are assembled in our state-of-the-art facilities in Lawrenceville, IL and Burleson, TX. Replacement parts are quickly fulfilled from our Burleson, TX location and shipped to anywhere in North America.

\*Wagner-Smith Equipment Co. reserves the right to change the specification of any unit at any time without prior notice. This spec sheet is only a statement of general specifications on the date of this publication.

To learn more or find a location nearest you, please visit **WagnerSmith.com**



**Wagner  
Smith**  
Equipment Co.

**41075-19R**

REV. 2023