

T-4RC-48x48



FEATURES

YOUR MULTIPLE REEL CARRIER TRAILER IS HERE; READY FOR THE LONG HAUL.

VE





CAPABLE TO CARRY REELS OR CONDUIT

A trailer mounted, four place reel carrier, designed to transport and tension cable or four conductor reels up to 48" in diameter, 48" wide, and weighing up to 3,085 pounds per reel. This unit is used for Distribution only.

Reel spindles may incorporate an optional mechanical manual rewind to allow the operator to rewind conductor via a hand crank or external hydraulic supply when job is completed. QUICK CHANGE SPINDLES, REQUIRE NO TOOLS

VERSATILITY IN SIZE OF SPOOLS

DESIGNED FOR OPTIMAL PERFORMANCE AND SAFETY



T-4RC-48x48 SPECIFICATIONS

STANDARD FEATURES	
Front Hitch	Adjustable 3" lunette eye
Lighting	DOT regulation LED
Electrical Plug	6 way pin
Jacks	Front manual crank/Rear pin type
Tires	215/75R17.5 Load Range "H"
Axles	Tandem 8,000 lb. capacity each
Suspension	Slipper leaf spring
Brakes	Electric with breakaway switch
Wheel Chocks	Standard
Ground Lugs	Front/Rear mounted
Tie Downs	Front/Rear frame mounted
UNIT PERFORMANCE - REEL CARRIER	
	4
Max. Reel Diameter	4 48"
Max. Reel Diameter Max. Reel Width	
	48"
Max. Reel Width	48" 48"
Max. Reel Weight	48" 48" 3,085 lbs. each
Max. Reel Width Max. Reel Weight Spindle Diameter	48" 48" 3,085 lbs. each 2 3/4"
Max. Reel Width Max. Reel Weight Spindle Diameter Reel Loading	48" 48" 3,085 lbs. each 2 3/4" Quick lift, no tools required
Max. Reel Width Max. Reel Weight Spindle Diameter Reel Loading Reel Brakes	48" 48" 3,085 lbs. each 2 3/4" Quick lift, no tools required
Max. Reel Width Max. Reel Weight Spindle Diameter Reel Loading Reel Brakes DIMENSIONS & WEIGHT	48" 48" 3,085 lbs. each 2 3/4" Quick lift, no tools required Manually actuated caliper with 16" disc
Max. Reel Width Max. Reel Weight Spindle Diameter Reel Loading Reel Brakes DIMENSIONS & WEIGHT L X W X H	48" 48" 3,085 lbs. each 2 3/4" Quick lift, no tools required Manually actuated caliper with 16" disc 27'3" x 8' x 6'
Max. Reel Width Max. Reel Weight Spindle Diameter Reel Loading Reel Brakes DIMENSIONS & WEIGHT L X W X H Net Weight	48" 48" 3,085 lbs. each 2 3/4" Quick lift, no tools required Manually actuated caliper with 16" disc 27'3" x 8' x 6' 5,740 lbs.
Max. Reel Width Max. Reel Weight Spindle Diameter Reel Loading Reel Brakes DIMENSIONS & WEIGHT L X W X H Net Weight GVWR	48" 48" 3,085 lbs. each 2 3/4" Quick lift, no tools required Manually actuated caliper with 16" disc 27'3" x 8' x 6' 5,740 lbs. 18,800 lbs.



EQUIPPED LOCATIONS NATIONWIDE

 \odot

f

All equipment is available for purchase and rental through our five locations across the USA. We want to be prepared for all of your demands because we are dedicated to helping the industry whenever you need it.

(in)

ASSEMBLED IN THE USA

All Wagner-Smith Equipment Co. equipment are assembled in our state-of-the-art facilities in Lawrenceville, IL and Burleson, TX. Replacement parts are quickly fulfilled from our Burleson, TX location and shipped to anywhere in North America.

*Wagner-Smith Equipment Co. reserves the right to change the specification of any unit at any time without prior notice. This spec sheet is only a statement of general specifications on the date of this publication.







REV. 2023