

**Wagner
Smith
Equipment Co.**

T-5DP-120-FT4



HEAVY DUTY, FIVE DRUM PULLER FOR ALL YOUR TRANSMISSION NEEDS.



PULLING OPERATIONS ALL DONE AT THE OPERATORS STAND FOR SAFETY.

Internally pressure compensated closed-loop hydraulic system, minimizes heat build up of hydraulic fluid, can preset desired pulling pressure.



Spring applied, hydraulic pressure released safety brake is standard in the main drive line for operator safety. All unit operating controls are located at the operator's station, off the ground, for operator safety.



Each drum can be disconnected for freewheeling with brake over spin (manual) control. Drum brakes.

FEATURES

TOUCH SCREEN OPERATING PANEL

UP TO 22,000' LINE CAPACITIES

USED IN A RANGE OF TRANSMISSION APPLICATIONS

APPROXIMATE LINE CAPACITY

22,000' 3/8" Amsteel Blue

41120-12R

T-5DP-120-FT4 SPECIFICATIONS

STANDARD FEATURES	
Diesel Engine	115HP FT4
Hydraulic Tank	7 gallons
Levelwind	Post type with swing top roller, hydraulically operated
Front Hitch	Fifth Wheel
Electrical Connection	7 pole plug with spring cable
Suspension	2 supplied on mounting tubes
Lighting	D.O.T. regulation LED
Tires	255/70R22.5 with Load rating "G"
Axles	Tandem 25,000 lbs. each
Suspension	Slipper leaf spring
Brakes	Air with ABS front axle
Jacks	Front and Rear
Wheel Chocks	Supplied
Tie Downs	3 1/2" ID Ears
UNIT PERFORMANCE <i>(figures for a single drum pulling. Levelwind designed for pulling with one drum at a time)</i>	
Continuous Torque Rating	120,000 in. lbs.
Line Speed (average)	4 mph.
Full Drum Line Pull Rating	4,000 lbs.
ROPE PULLING REEL	
Reel	5
Diameter	60"
Inside Width	40"
Core Diameter	24"
Approximate Line Capacity	22,000' 3/8" Amsteel Blue
DIMENSIONS & WEIGHT	
L X W X H	42'6" x 8' x 11'7"
Net Weight	39,080 lbs.
GVWR	56,000 lbs.
GAWR	45,400 lbs.
COMBO OPTION: STEEL (3 REELS) & AMSTEEL BLUE (2 REELS)	
GVWR	63,000 lbs.
GAWR	39,500 lbs.
Tongue Weight	23,500 lbs.
Approximate Line Capacity	(2) Outboard Reels: 22,000' 3/8" Amsteel Blue
	(3) Inboard Reels: 22,000' 3/8" Steel Rope



EQUIPPED LOCATIONS NATIONWIDE

All equipment is available for purchase and rental through our five locations across the USA. We want to be prepared for all of your demands because we are dedicated to helping the industry whenever you need it.

ASSEMBLED IN THE USA

All Wagner-Smith Equipment Co. equipment are assembled in our state-of-the-art facilities in Lawrenceville, IL and Burleson, TX. Replacement parts are quickly fulfilled from our Burleson, TX location and shipped to anywhere in North America.

*Wagner-Smith Equipment Co. reserves the right to change the specification of any unit at any time without prior notice. This spec sheet is only a statement of general specifications on the date of this publication.

To learn more or find a location nearest you, please visit **WagnerSmith.com**



**Wagner
Smith**
Equipment Co.

41120-12R

REV. 2023