



## MULTIPLE OPTIONS OF USE WITH TRANSPORTING CAPABILITIES.



### FOR BOTH TRANSMISSION AND DISTRIBUTION CAPABILITIES

Quick change type reel and spindle assemblies lift straight out of the unit without having to shift to the side. No tools are required for reel removal.



All unit operating controls are located at the operator's station, off the ground, for operator safety. A fairlead roller assembly is provided as standard.



Designed with canted bullwheels to reduce twist on conductor.

## FEATURES

EASY LIFT REEL SPINDLES  
FOR REPLACEMENT

USE FOR TRANSMISSION  
OR DISTRIBUTION

FAIRLEAD ROLLER  
ASSEMBLY PROVIDED

**46052-10R**

# T-BWT-5-52-RC SPECIFICATIONS

STANDARD FEATURES	
Tension Brakes	Hydraulically actuated 42" diameter caliber
Reel Brakes	Hydraulically actuated 20" diameter caliber
Front Hitch	Adjustable 3" lunette eye
Lighting	DOT regulation LED
Electrical Plug	6 way pin
Jacks	Front & Rear manual
Tires	215/75/R17.5 Load Range "H"
Axle	Tandem 8,000 lb. capacity
Suspension	Leaf spring
Brakes	Electric with breakaway switch
Tie Downs	Front and rear mounted
Grounding	Mounted front and rear lugs
Wheel Chocks	Standard
UNIT PERFORMANCE	
Maximum Tension Rating	5,000 lbs.
Line Speed	4 mph.
BULLWHEEL TENSIONER	
Diameter	52" (bottom of groove)
Groove Diameter	1.50"
Number of Grooves	5
Replacement Segments	Yes
Bullwheel Lining	Elastomer (bolt on)
REEL CARRIER	
Quantity	1
Max. Reel Diameter	96"
Max. Reel Width	56"
Max. Reel Weight	10,000 lbs.
Spindle Diameter	2 3/4" complete with locking collars
DIMENSIONS & WEIGHT	
L X W X H	20'6" x 8' x 9'9"
Net Weight	7,400 lbs.
GVWR	18,368 lbs.
GAWR	16,000 lbs.
Tongue Weight	2,600 lbs.



## EQUIPPED LOCATIONS NATIONWIDE

All equipment is available for purchase and rental through our five locations across the USA. We want to be prepared for all of your demands because we are dedicated to helping the industry whenever you need it.

## ASSEMBLED IN THE USA

All Wagner-Smith Equipment Co. equipment are assembled in our state-of-the-art facilities in Lawrenceville, IL and Burleson, TX. Replacement parts are quickly fulfilled from our Burleson, TX location and shipped to anywhere in North America.

\*Wagner-Smith Equipment Co. reserves the right to change the specification of any unit at any time without prior notice. This spec sheet is only a statement of general specifications on the date of this publication.

To learn more or find a location nearest you, please visit **WagnerSmith.com**



**Wagner  
Smith**  
Equipment Co.

**46052-10R**

REV. 2023