

YOUR SINGLE REEL CARRIER TRAILER IS HERE; READY FOR THE LONG HAUL.



CAPABLE TO CARRY REELS OR CONDUIT

This no hassle maintenance trailer is perfect for hauling both reels and conduit at the same time. With max reel diameters of up to 96", this trailer is ready for your job.

Quick change spindles lift straight out, requiring no tools. All wiring is protected by the frame and is engineered for optimum performance and safety.



QUICK CHANGE SPINDLES, REQUIRE NO TOOLS

VERSATILITY IN SIZE OF SPOOLS

DESIGNED FOR OPTIMAL PERFORMANCE AND SAFETY





47096-6DR

T-RC-96x54-12 SPECIFICATIONS

| STANDARD FEATURES | |
|---------------------------------|---|
| Front Hitch | Adjustable 3" lunette eye |
| Lighting | DOT regulation LED |
| Electrical Plug | 6 way pin |
| Jacks | Front/Rear manual crank |
| Tires | 215/75R17.5 Load range "H" |
| Axles | Tandem 8,000 lbs. each |
| Suspension | Slipper leaf spring |
| Wheel Chocks | Standard |
| Brakes | Electric with breakaway switch |
| Grounding Lugs | Front/Rear mounted |
| Tie Downs | Front/Rear mounted on frame |
| Brake Disc | ASTM 588 steel |
| UNIT PERFORMANCE - REEL CARRIER | |
| Quantity | 1 |
| Max. Reel Diameter | 96" |
| Max. Reel Width | 54" |
| Trailer Payload Rating | 12,000 lbs. |
| Spindle Diameter | 2 1/2" with locking collars |
| Reel Loading | Quick lift, no tools required |
| Reel Brakes | Hydraulically actuated caliper 20" disc |
| DIMENSIONS & WEIGHT | |
| LXWXH | 16'5" x 8' x 6'8" |
| Net Weight | 3,180 lbs. |
| GVWR | 16,400 lbs. |
| GAWR | 16,000 lbs. |
| Tongue Weight Empty | 360 lbs. |



EQUIPPED LOCATIONS NATIONWIDE

All equipment is available for purchase and rental through our five locations across the USA. We want to be prepared for all of your demands because we are dedicated to helping the industry whenever you need it.

ASSEMBLED IN THE USA

All Wagner-Smith Equipment Co. equipment are assembled in our state-of-the-art facilities in Lawrenceville, IL and Burleson, TX. Replacement parts are quickly fulfilled from our Burleson, TX location and shipped to anywhere in North America.

*Wagner-Smith Equipment Co. reserves the right to change the specification of any unit at any time without prior notice. This spec sheet is only a statement of general specifications on the date of this publication.



To learn more or find a location nearest you, please visit **WagnerSmith.com**

47096-6DR









