



TRANSPORT AND TENSION ALL IN ONE UNIT.



SMOOTH RUNNING HYDRAULIC CALIPERS

Quick change type reel and spindle assemblies lift straight out of the unit without having to shift to the side. No tools are required for reel removal.



All unit operating controls are located at the operator's station, off the ground, for operator safety.

Corrosion resistant steel brake discs are standard for smooth operation and low maintenance.



A fairlead roller assembly is provided as standard.

FEATURES

QUICK CHANGE SPINDLE ASSEMBLY

ALLOWS FOR UP TO 84" REELS

SINGLE REEL CARRIER WITH FAIRLEAD ASSEMBLY

46036-10R

T-VBWT-3-36-RC SPECIFICATIONS

STANDARD FEATURES	
Tension Brakes	Hydraulically actuated 30" diameter caliber
Reel Brakes	Hydraulically actuated 20" diameter caliber
Front Hitch	Adjustable 3" lunette eye
Lighting	DOT regulation LED
Electrical Plug	6 way pin
Jacks	Front & Rear manual
Tires	9.50x16.5 Load Range "E"
Grounding Lugs	Front & Rear mounted
Axle	Tandem 6,000 lb. capacity
Suspension	Leaf spring
Brakes	Electric with breakaway switch
Tie Downs	Front and rear mounted
Arbor Bushing Spindle	Arbor bushing with holders for each
Brake Disc	ASTM 588 steel
Wheel Chocks	Standard
UNIT PERFORMANCE	
Maximum Tension Rating	3,000 lbs.
Line Speed	4 mph.
BULLWHEEL TENSIONER	
Diameter	35" (bottom of groove)
Number of Grooves	1
Replacement Segments	Yes
DIMENSIONS & WEIGHT	
L X W X H	17'7" x 8' x 8'3"
Net Weight	4,260 lbs.
GVWR	13,200 lbs.
GAWR	12,000 lbs.
Tongue Weight	1,280 lbs.



EQUIPPED LOCATIONS NATIONWIDE

All equipment is available for purchase and rental through our five locations across the USA. We want to be prepared for all of your demands because we are dedicated to helping the industry whenever you need it.

ASSEMBLED IN THE USA

All Wagner-Smith Equipment Co. equipment are assembled in our state-of-the-art facilities in Lawrenceville, IL and Burleson, TX. Replacement parts are quickly fulfilled from our Burleson, TX location and shipped to anywhere in North America.

*Wagner-Smith Equipment Co. reserves the right to change the specification of any unit at any time without prior notice. This spec sheet is only a statement of general specifications on the date of this publication.

To learn more or find a location nearest you, please visit **WagnerSmith.com**



**Wagner
Smith**
Equipment Co.

46036-10R

REV. 2023