

POWER REEL ROLLER FOR THOSE LARGER AND NON TYPICAL REELS.



A DANGER



PERFECT FOR TAKE-UP OR PAYOUT

This electric powered reel roller has a variety of options for the take-up or payout of conductor or rope. It can be mounted to a flat bed truck or trailer as well as placed on the ground.

With the adjustable rollers, the units permits the use of reels up to 156" wide all the way down to 30". It is equipped with integral forklift lifting points for safe transport and placement.

The ease of use with an on/off foot actuated control switch as well as a panel mounted speed control.

ADJUSTABLE ROLLERS TO ACCOMMODATE LARGER REELS UP TO 156"

INTEGRATED FORKLIFT LIFTING POINTS

43035-10R

CRR-35 SPECIFICATIONS

STANDARD FEATURES	
Electrical Power Required	110-120 VAC, 15 amps
Speed Control	Panel mounted 0-70 rpm
Reverse Switch	Panel mounted
Control Switch	Foot pedal on/off
Reel Tie Down	17/8"
Unit Tie Down	11/2"
UNIT PERFORMANCE	
Max. Reel Diameter	156"
Max. Reel Width	100"
Max. Reel Weight	35,000 lbs.
Roller Diameter	6"
Roller Flange Diameter	15" Driver Roller, 11 1/2" Idler Roller
DIMENSIONS & WEIGHT	
LXWXH	69" x 116" x 22"
Net Weight	2,500 lbs.



EQUIPPED LOCATIONS NATIONWIDE

All equipment is available for purchase and rental through our five locations across the USA. We want to be prepared for all of your demands because we are dedicated to helping the industry whenever you need it.

ASSEMBLED IN THE USA

All Wagner-Smith Equipment Co. equipment are assembled in our state-of-the-art facilities in Lawrenceville, IL and Burleson, TX. Replacement parts are quickly fulfilled from our Burleson, TX location and shipped to anywhere in North America.

*Wagner-Smith Equipment Co. reserves the right to change the specification of any unit at any time without prior notice. This spec sheet is only a statement of general specifications on the date of this publication.



To learn more or find a location nearest you, please visit **WagnerSmith.com**











43035-10R